


FLOW METER:	BUBBLER
CONNECTION:	12" DIA. CPVC PIPE
ACCESSORIES:	STAINLESS STEEL BUBBLE TUBE

PLAN VIEW
(GAS TIGHT HATCH NOT SHOWN FOR CLARITY)

ELEVATION VIEW

- 1) FLOW IS FROM LEFT TO RIGHT
- 2) ANCHOR BOLTS BY OTHERS
- 3) FLOW ENTERING THE FLUME MUST BE SUBCRITICAL
- 4) FILL VOID BETWEEN MANHOLE BARREL WALL AND OUTSIDE OF EFFLUENT CONTAINMENT AREA
- 5) FILL - WITHOUT VOIDS - AREA UNDER H-FLUME APPROACH SECTION PRIOR TO BACKFILLING REST OF MANHOLE - FAILURE TO SUFFICIENTLY BACKFILL UNDER APPROACH SECTION MAY RESULT IN FLUME FAILURE

 TRACOM FIBERGLASS PRODUCTS	METERING MANHOLE, 48 INCH DIA., ALUMINUM HATCH STYLE, 30" W X 24" D GAS-TIGHT HATCH, 1.5' H-FLUME, 12" PIPE STUBS, AND BUBBLE TUBE (LEFT)	
	DWG. NO. MH-48-ALGT30X24-H15-P12-N-BL-N-N-N	REV 2
PROJECT LEPRINO FOODS MMH-3 GREELEY, CO	DATE 12/2/10	